

Novaflex 3550 Heavier Duty Petroleum Discharge Hose



Designed to be flexible with a hose cover that provides extra abrasion resistance to meet the demanding requirements of industry. Handles all grades of petroleum with aromatic contents to 55%.

Construction:

Tube: Black Nitrile

Reinforcement: Multiple plies tire cord with static wire.

Cover: Red oil and abrasion resistant rubber

Length: 100 ft.

Temperature Range: -30°F to +180°F

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3550BT-01000-00	1	1.52	2	n/a	n/a	250	0.57
3550BT-01500-00	1 1/2	2.14	2	n/a	n/a	250	0.96
3550BT-02000-00	2	2.64	2	n/a	n/a	250	1.23
3550BT-02500-00	2 1/2	3.14	2	n/a	n/a	250	1.49
3550BT-03000-00	3	3.54	2	n/a	n/a	250	2.10
3550BT-04000-00	4	4.65	4	n/a	n/a	250	2.42
3550BT-06000-00	6	6.70	4	n/a	n/a	250	4.90

Novaflex 3375 Novaflex 3376 Fuel Transfer and Fill Hose



Designed for fuel fill applications. Economical Novaflex 3375 exceeds the SAEJ1527 with a flame retardant cover but is not recommended for marine service. Novaflex 3376 meets the SAE 1527 B2 requirements and is branded to the specification. It does not have a

Construction:

Tube: Nitrile.

Reinforcement: Fabric with helix wire.

Cover: Smooth Black Neoprene.

Length: 50 ft and 100ft lengths.

Temperature Range: -30°F to +180°F

Part No.	I.D.	O.D.	WP psi	MBR (in)	WT LBS/FT
3375-00500-00	1/2	0.85	40	2 1/2	0.24
3375-00625-00	5/8	0.98	40	2 1/2	0.27
3375-00750-00	3/4	1.10	40	2 1/2	0.29
3375-00875-00	7/8	1.23	40	3	0.34
3375-01000-00	1	1.35	40	3	0.37
3375-01125-00	1 1/8	1.48	40	3	0.41
3375-01225-00	1 1/4	1.60	40	3	0.48
3375-01313-00	1 5/16	1.66	40	3 1/2	0.52
3375-01375-00	1 3/8	1.73	40	4	0.54
3375-01500-00	1 1/2	1.85	20	4	0.59
3375-01625-00	1 5/8	1.98	20	5	0.62
3375-01750-00	1 3/4	2.10	20	5	0.67
3375-01875-00	1 7/8	2.23	20	5	0.70
3375-02000-00	2	2.37	20	6	0.80
3375-02125-00	2 1/8	2.49	20	6	0.88
3375-02225-00	2 1/4	2.62	20	6 1/2	0.90
3375-02375-00	2 3/8	2.74	20	7	0.92
3375-02500-00	2 1/2	2.87	20	8	1.00
3375-02625-00	2 5/8	2.99	20	9	1.05
3375-02750-00	2 3/4	3.12	20	10	1.10
3375-02875-00	2 7/8	3.31	20	11	1.13
3375-03000-00	3	3.44	20	13	1.18
3375-03225-00	3 1/4	3.69	20	15 1/2	1.36
3375-03500-00	3 1/2	3.94	20	16	1.44
3375-04000-00	4	4.44	20	18	1.59
3375-04500-00	4 1/2	4.95	20	24	1.85
3375-05000-00	5	5.45	20	32	2.04
3375-06000-00	6	6.45	20	36	2.36