

Steam Hose



Novaflex 5510 Black Low Pressure Conductive Steam Hose 100psi



This textile reinforced steam hose is an excellent flexible light weight hose for transferring steam in medium temperature applications.

Construction:

Tube: Black EPDM

Reinforcement: Plies of fiberglass tire cord

Cover: Smooth black weather and abrasion resistant EPDM

Length: 100 ft.

Temperature Range: up to 338°F

Part No.	I.D.	O.D.	Plies Fiberglass	WP psi	WT LBS/ FT
5510BE-00500-00	1/2	1.02	4	100	0.34
5510BE-00750-00	3/4	1.27	4	100	0.45
5510BE-01000-00	1	1.52	4	100	0.56
5510BE-01250-00	1 1/4	1.82	4	100	0.75
5510BE-01500-00	1 1/2	2.07	4	100	0.87
5510BE-02000-00	2	2.57	4	100	1.11

Novaflex 5520 Red Low Pressure Non- Conductive Steam Hose 100psi



This textile reinforced steam hose is an excellent flexible light weight hose for transferring steam in medium temperature applications that require an electrically conductive hose.

Construction:

Tube: Red EPDM rubber

Reinforcement: Plies of fiberglass tire cord

Cover: Smooth Red weather and abrasion resistant EPDM rubber

Length: 100 ft.

Temperature Range: up to 338°F

Non-conductive

Part No.	I.D.	O.D.	Plies Fiberglass	WP psi	WT LBS/ FT
5520RE-00500-00	1/2	1.02	4	100	0.34
5520RE-00750-00	3/4	1.27	4	100	0.45
5520RE-01000-00	1	1.52	4	100	0.56
5520RE-01250-00	1 1/4	1.82	4	100	0.75
5520RE-01500-00	1 1/2	2.07	4	100	0.87
5520RE-02000-00	2	2.57	4	100	1.11
5520RE-03000-00	3	3.76	6	100	2.19

Novaflex 2145 Hot Water Washdown Hose White oil resistant non marking cover



An excellent, long lasting washdown hose designed for the rugged requirement found in the food processing industry.

Construction:

Tube: White EPDM

Reinforcement: Polyester Tire Cord

Cover: White Nitrile

Length: 100 ft.

Temperature Range: -30°F to 210°F
(not rated for steam)

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2145WE-00750-01	3/4	1.25	2	250	.44
2145WE-01000-01	1	1.54	4	250	.62
2145WE-01250-01	1 1/4	1.79	4	250	.74
2145WE-01500-01	1 1/2	2.04	4	250	.86