

## Novaflex 2151 Heavy Duty Hot Water Washdown Hose



Designed to meet the rugged washdown applications in the food processing industry.

### Construction:

Tube: White EPDM

Reinforcement: Multiple layers of polyester cord

Cover: White EPDM non marking.

Length: 100ft.

Temperature Range: -40° to 212°F

Not rated for steam

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/Ft
2151WE-00750-00	3/4	1.31	4	300	0.44
2151WE-01000-00	1	1.56	4	300	0.54
2151WE-01250-00	1 1/4	1.81	4	300	0.65

## Novaflex 170 Layflat Water Discharge Hose



This light blue waster discharge hose is designed to meet the requirements of the pump industry. It is both lightweight and rugged enough to provide excellent service in the construction, rental and other general industry discharge applications.

### Construction:

Tube: PVC

Reinforcement: Polyester cord

Cover: Light blue PVC

Length: 100ft.

Temperature Range: -10° to 150°F

Part No.	I.D.	O.D.	Max WP @ 68°F	Length Roll	WT LBS/Ft
7PVCLFS01.08	1 1/2	1.75	70	300	0.19
7PVCLFS02.00	2	2.21	65	300	0.25
7PVCLFS03.00	3	3.21	55	300	0.44
7PVCLFS04.00	4	4.27	55	300	0.48

## Novaflex 171 Layflat Heavy Duty Water Discharge Hose



A heavy duty red water discharge hose designed to meet the more rugged requirements of the pump industry. It has a high working pressure with improved bulk to resist the common abuses a lighter weight hose may not tolerate. This heavyweight hose offers an economical alternative for longer hose life.

### Construction:

Tube: PVC

Reinforcement: Polyester cord

Cover: Red PVC

Length: 100ft.

Temperature Range: -10° to 150°F

Part No.	I.D.	O.D.	Max WP @ 68°F	Length Roll	WT LBS/Ft
7PVCLFH01.08	1 1/2	1.77	115	300	0.27
7PVCLFH02.00	2	2.23	115	300	0.37
7PVCLFH03.00	3	3.23	85	300	0.42
7PVCLFH04.00	4	4.27	85	300	0.57
7PVCLFH06.00	6	6.32	70	300	0.91
7PVCLFH08.00	8	8.32	70	300	1.28

# Water Hose

## Novaflex 2152 Water Suction Hose



This heavy duty water suction hose is designed for use on portable pumps by contractors, quarries and mine sites.

**Construction:**

Tube: Black synthetic EPDM rubber

Reinforcement: Plies of polyester tire cord with wire helix


Cover: Smooth black weather and abrasion resistant rubber

Length: 100ft.

Temperature Range: -30° to 180°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2152BE-00750-00	¾	1.11	2	300	0.39
2152BE-01000-00	1	1.36	2	300	0.50
2152BE-01250-00	1¼	1.61	2	300	0.60
2152BE-01500-00	1½	1.86	2	250	0.70
2152BE-02000-00	2	2.43	2	200	1.13
2152BE-02500-00	2½	2.93	2	175	1.38
2152BE-03000-00	3	3.43	2	150	1.63
2152BE-03500-00	3½	3.99	2	125	2.37
2152BE-04000-00	4	4.49	2	100	2.70
2152BE-05000-00	5	5.58	2	100	4.31
2152BE-06000-00	6	6.65	2	75	5.81
2152BE-08000-00	8	8.74	2	75	8.36
2152BE-10000-00	10	10.85	2	75	13.47
2152BE-12000-00	12	12.95	4	75	17.52

## Novaflex 2226 Heavy Duty Water Discharge Hose



A heavy duty water discharge hose for the toughest industrial or construction applications. The cover is designed to withstand weather, abrasion and ozone.

**Construction:**

Tube: Black synthetic EPDM rubber

Reinforcement: 4ply polyester tire cord

Cover: Smooth black weather and abrasion resistant rubber

Length: 100ft.

Temperature Range: -40°F to 180°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2226BE-01500-00	1½	2.04	4	300	0.84
2226BE-02000-00	2	2.54	4	250	1.08
2226BE-02500-00	2½	3.04	4	250	1.32
2226BE-03000-00	3	3.54	4	200	1.56
2226BE-04000-00	4	4.54	4	200	2.04
2226BE-05000-00	5	5.54	4	200	2.53
2226BE-06000-00	6	6.58	4	200	2.96
2226BE-08000-00	8	8.58	4	200	4.10
2226BE-10000-00	10	10.58	4	150	5.08
2226BE-12000-00	12	12.61	4	150	6.53

## Novaflex 2636 Slip Ring / Coupler Rubber Water Hose



A lightweight layflat water discharge hose which is connected without couplings. The hose is built with a male and female end enabling the user to connect hoses. The male end is inserted into the female end and locked into place with a steel ring. The hoses can be easily connected and disconnected in the field without tools. Ideal for dewatering applications, irrigation, light dredging, etc.

**Construction:**

Tube: Black synthetic EPDM rubber

Reinforcement: Multiple plies polyester tire cord.

Cover: Black synthetic rubber.

Length: 50 ft.

Temperature Range: -40°F to 180°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2636BE-04000-00	4	4.22	2	100	40
2636BE-06000-00	6	6.22	2	75	62
2636BE-08000-00	8	8.22	2	65	79
2636BE-10000-00	10	10.22	2	50	96
2636BE-12000-00	12	12.20	2	40	120
2636BE-14000-00	14	14.22	2	35	135
2636BE-16000-00	16	16.22	2	35	163
2636BE-24000-00	24	24.22	2	30	235

# Water Hose

## Novaflex 2140 Papermill Washdown Hose with Nozzle 50ft. lengths



A quality wash down hose used in paper mills and other industrial applications. Supplied with integral tapered nozzle built to end.

### Construction:

Tube: Black synthetic rubber

Reinforcement: plies of polyester tire cord

Cover: Green weather and abrasion resistant rubber supplied with integral tapered rubber nozzle built into end. (Optional colors available)

Length: 50ft (lengths up to 100ft available on request)

Temperature Range: -30° to 200°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/ FT
2140BE-05000-61	½	0.91	2	200	0.28
2140BE-00750-61	¾	1.16	2	200	0.38
2140BE-01000-61	1	1.42	2	200	0.50
2140BE-01250-61	1¼	1.77	2	150	0.78
2140BE-01500-61	1½	2.06	2	150	0.99

## Novaflex 2150 Water Discharge Hose



A lightweight rubber water discharge hose designed for use on portable pumps by contractors and municipalities.

### Construction:

Tube: Black synthetic EPDM rubber

Reinforcement: Plies of polyester tire cord

Cover: Smooth black weather and abrasion resistant rubber

Length: 100ft.

Temperature Range: -30° to 180°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/ FT
2150BE-01250-00	1¼	1.44	2	300	0.40
2150BE-01500-00	1½	1.69	2	250	0.47
2150BE-02000-00	2	2.19	2	200	0.62
2150BE-00250-00	2½	2.69	2	150	0.76
2150BE-03000-00	3	3.19	2	125	0.91
2150BE-03500-00	3½	3.74	2	125	1.05
2150BE-04000-00	4	4.24	2	100	1.19
2150BE-05000-00	5	5.32	2	100	1.49
2150BE-06000-00	6	6.32	2	85	1.78
2150BE-06250-00	6 5/8	6.94	2	75	1.97
2150BE-08000-00	8	8.33	2	75	2.54
2150BE-08625-00	8 5/8	8.95	2	75	2.89
2150BE-10000-00	10	10.43	4	75	4.19
2150BE-10750-00	10¾	11.18	4	75	4.51
2150BE-12000-00	12	12.43	4	75	5.02
2150BE-12750-00	12¾	13.18	4	75	5.33

## Novaflex 2200 Water Jetting Hose



Designed for extremely flexible, lightweight high pressure water jetting hose. Premium cover provides protection against cuts, gouging, scuffs and ozone.

**Construction:**

Tube: Black EPDM  
 Reinforcement: Polyester tire cord  
 Cover: Smooth black EPDM cover  
 Length: 100ft.  
 Temperature Range: -30° to 180°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2200BE-02000-00	2	2.48	2	500	0.91
2200BE-02500-00	2 1/2	3.08	4	500	1.34
2200BE-03000-00	3	3.61	4	400	1.59
2200BE-04000-00	4	4.61	4	300	2.07

## Novaflex 2250 High Pressure Water Jetting Hose




Designed for heavy duty, high pressure water jetting. Premium quality compounds provide excellent resistance to the common abuses associated with water jetting in the marine and construction industry.

**Construction:**

Tube: Black EPDM  
 Reinforcement: Polyester tire cord  
 Cover: Smooth black EPDM cover  
 Length: 100ft  
 Temperature Range: -30° to 180°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2250BE-02000-00	2	2.70	6	800	1.30
2250BE-02500-00	2 1/2	3.24	6	800	1.59
2250BE-03000-00	3	3.74	6	800	1.87
2250BE-04000-00	4	4.74	6	800	2.42
2250BE-05000-00	5	5.74	6	500	2.68
2250BE-06000-00	6	6.74	6	500	3.20

## Novaflex 2019 Coolant Hose



Designed for heavy duty industrial or automotive coolant service.

The 3 ply construction hose has a specially blended tube compound designed to resist heat and oil.

### Construction:

Tube: Black EPDM

Reinforcement: Plies of fabric

Cover: Black EPDM

Length: Available in 50 ft lengths.


Temperature Range: -40°F to 200°F

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/ FT
2019BE-06250-70	5/8	1.00	3	130	0.34
2019BE-07500-70	¾	1.13	3	115	0.38
2019BE-08750-70	7/8	1.25	3	100	0.42
2019BE-01000-70	1	1.38	3	90	0.46
2019BE-01125-70	1 1/8	1.50	3	80	0.50
2019BE-01225-70	1¼	1.38	3	75	0.55
2019BE-01312-70	1 5/16	1.75	3	70	0.59
2019BE-01375-70	1 3/8	1.69	3	70	0.57
2019BE-01500-70	1½	1.88	3	65	0.63
2019BE-01625-70	1 5/8	2.00	3	60	0.67
2019BE-01750-70	1¾	2.13	3	55	0.71
2019BE-01875-70	1 7/8	2.25	3	55	0.76
2019BE-02000-70	2	2.38	3	50	0.80
2019BE-02125-70	2 1/8	2.50	3	45	0.84
2019BE-02225-70	2¼	2.63	3	45	0.88
2019BE-02375-70	2 3/8	2.75	3	40	0.92
2019BE-02500-70	2½	2.88	3	40	0.96
2019BE-02625-70	2 5/8	3.00	3	40	1.01
2019BE-02750-70	2¾	3.13	3	35	1.05
2019BE-02875-70	2 7/8	3.25	3	35	1.09
2019BE-03000-70	3	3.38	3	35	1.13
2019BE-03125-70	3 1/8	3.50	3	30	1.17
2019BE-03225-70	3¼	3.63	3	30	1.22
2019BE-03500-70	3½	3.88	3	30	1.30
2019BE-04000-70	4	4.38	3	25	1.47
2019BE-04500-70	4½	4.88	3	25	1.63
2019BE-04750-70	4¾	5.13	3	20	1.72
2019BE-05000-70	5	5.38	3	20	1.80
2019BE-05500-70	5½	5.88	3	20	1.97

# Water Hose - Fire Engine Suction



## Novaflex 2160 Water Removal and Hydrant Services



Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks

**Construction:**

Tube: SBR

Reinforcement: Multiple plies of polyester tire cord with helix

Cover: Smooth SBR

Length: Available in specific lengths with cuff ends - price on application

Temperature Range: -40° to 180°F

Meets or exceeds NFPA #189 & 1901 requirements

Part No.	I.D.	O.D.	Plies	WP psi	Min Order Lgth	WT LBS/ FT
2160BS-02500-00	2	3.25	2	150	100'	2.46
2160BS-03000-00	2 1/2	3.687	2	150	100'	2.88
2160BS-04000-00	3	4.25	2	150	50'	3.77
2160BS-04500-00	4	4.687	4	150	50'	5.16
2160BS-05000-00	5	5.75	4	150	50'	5.77
2160BS-06000-00	6	6.75	4	150	50'	7.03

## Novaflex 2161 Water Removal and Hydrant Services



Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks.

**Construction:**

Tube: SBR

Reinforcement: Multiple plies of polyester tire cord with helix

Cover: Corrugated black EPDM cover

Length: up to 100 ft

Temperature Range: -40° to 180°F

Hose comes with 6" cuffed ends. Meets or exceeds NFPA #189 & 1901 requirements.

Part No.	I.D.	O.D.	Plies	WP psi	Min Qty	WT LBS/ FT
2161BS-02500-00	2	3.04	2	150	4	2.42
2161BS-03000-00	2 1/2	3.54	2	150	4	2.9
2161BS-04000-00	3	4.54	2	150	2	3.47
2161BS-04500-00	4	4.687	4	159	2	5.2
2161BS-05000-00	5	5.54	4	150	2	5.88
2161BS-06000-00	6	6.58	4	150	2	7.36