

Novaflex U-Lok 440

Ultra Flexible Silicone Fiberglass Exhaust Extraction Duct



Applications

High temperature air supply and removal
Exhaust hose reels
Garage fume control
Combustion by-products

I.D.	Working Pressure/PSI	Negative Pressure Inch H.g
2"	24	20
3"	19	14
4"	16	10
5"	14	8
6"	11	6
8"	7	3
10"	5	1.5
12"	4	1

due to continuous improvements, technical data subject to change without notice

Single-ply economical silicone/fiberglass duct designed for vehicular exhaust extraction and high temperature air transfer.

Ultra flexible mechanical lock construction provides superior tear and tensile strength and eliminates wire movements found in traditional single-ply duct.

Air tight construction.

Uniform flexibility and compressibility reduces exhaust turbulence and pressure loss.

Construction

Material	Medium gauge silicone coated fiberglass
Construction	Mechanical lock, external steel scuff guard
Diameters	2" to 20"
Lengths	25ft
Weight	6" I.D. = 1.1lbs/ft
Temperature range	-60°F to +500°F (+600°F intermittent)
Compression ratio	5:1
Color	Orange/red with black external scuff guard

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336-578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Whitby, ON Tel 905.666.4970 Fax 905.666-9388 800.563.3539

THE
NOVAFLEX
GROUP



Email: sales@novaflex.com
Website: www.novaflex.com