



TODO® API COUPLINGS

TODO® API hose couplers and tank adaptors are interchangeable with other products manufactured to standard API RP 1004.

The TODO® API hose coupler is a high pressure design with five claw closure connection for strength and two interlocks for security and safety.

A moulded lip seal configuration is used for long leak-free performance.

TODO® API tank adaptors are available with or without operating handles or sightglasses.



FEATURES

- Connect and disconnect under pressure and without spillage.
- Built in accordance with API RP 1004.
- Mounting lugs provided for air interlock valve system.
- Optional sight glass on the adapter (tank unit).
- Flat surface area on the bottom portion of the valve, which prevents product from being trapped.
- The operating lever, body and sleeve are all of heavy-duty aluminium.
- Coupler is full interlocked. It cannot be opened unless it is properly connected, and cannot be disconnected when the poppet is open.

TECHNICAL DETAILS

| | |
|-------------------|---|
| Sizes: | 4" (DN 100). |
| Materials: | Aluminium alloy. |
| Seals: | FKM (Viton®). Other materials on request. |
| Working pressure: | PN 16. |
| Test pressure: | PN 24. |
| Safety factor: | 5:1. |
| End connections: | TW3/100 and TTMA flange |

Viton® and is a registered trademark of DuPont.

CERTIFICATES / APPROVALS

TODO® API couplings is built in accordance with API RP 1004.
ATEX compliant.
Manufactured under EN ISO 9001:2000.



API COUPLINGS RANGE



Coupler



Adaptor



Adaptor with handle

SPECIALS / ACCESSORIES



Air interlock valve



Dust plug



Dust cap



TODO® PRODUCTS OVERVIEW



TODO-MATIC® The first choice for the safe handling of hazardous, valuable or environmentally sensitive media. TODO-MATIC® are available in aluminium, gunmetal and stainless steel 316L with special materials such as hastelloy C276 available to order.
Sizes: 1" (DN 25) to 6" (DN 150).



TODO-GAS® The TODO-GAS® couplings are designed especially for the transfer of LPG in both liquid and vapour phases. The couplings are available in stainless steel and brass / gunmetal with thread or flange connection. Handling and operation are as simple as for the TODO-MATIC® DRY-BREAK® coupling.
Sizes: 1" (DN 25), 2" (DN 50) and 3" (DN 80).



TODO® SAFETY BREAK AWAY couplings Designed specifically to minimise spillage and damage associated with drive / pull away incidents. Also allows rapid removal of the mobile tankage in emergency situations. The coupling automatically senses an excessive load, closes its valves and then permits disconnection. Very high flow rate / low pressure drop. *Sizes: 2" (DN 50) and 3" (DN 80).*



TODO-45 aviation couplings An ISO 45 standard ground unit from TODO® and a special version of the TODO-MATIC® 2½" coupling available for connection to ground units conforming to standard ISO 45. This gives, for the first time, an economical alternative to ISO 45 standard hose couplers for aviation fuel transfers.



PTC - Safety Pressure Tight Cap The TODO® PTC is specifically designed to enhance operator safety and containment security in chemical and gas transport. Designed in close collaboration with leading chemical and gas companies, the PTC offers safety and operational benefits beyond those offered by existing closure technologies. *Sizes: 2" (DN 50) to 4" (DN 100).*



BALL VALVES These lightweight ball valves were the first products to be developed by TODO®. This valve offers obvious weight saving benefits for the road tanker industry but can also be used in a variety of plant applications. A wide selection of end connectors are available and valve changeover is rapid due to the simple sandwich design. All sizes are available with pneumatic actuation in either single or double acting form. *Sizes: 2" (DN 50) to 4" (DN 100).*



FUEL NOZZLES The TODO® fuel delivery nozzles are specifically designed to deliver high volumes with total security. Rugged cast aluminium alloy body, high strength swivel and robust handle all help this nozzle to offer reliable long term performance.
Size: 1½" (DN 40).



API couplings TODO® API hose couplers and tank adaptors are interchangeable with other products manufactured to standard API RP 1004. The TODO® hose coupler is a high pressure design with five claw closure connection for strength and two interlocks for security and safety. The moulded lipseal configuration is used for long leak-free performance. TODO® API tank adaptors are available with or without operating handles or sightglasses.
Size 4" (DN 100).



SWIVELS Developed originally as part of the TODO-MATIC® coupling construction then subsequently as a stand alone product, the TODO® swivel has proved itself in the toughest applications for over 20 years. Used mainly to allow free hose movement without imparting torque stresses to the assembly (one of the biggest causes of premature hose failure). *Sizes: ¾" (DN 19) to 4" (DN 100).*

TODO SE

Tel. Int.: +46 (0)506 19940
 Fax Int.: +46 (0)506 19944
 Email: todo@todo.se

TODO UK

Tel. Int.: +44 (0)1495 755 884
 Fax Int.: +44 (0)1495 752 505
 Email: todo@todo.co.uk

TODO NL

Tel. Int.: +31 (0)72 57 27880
 Fax Int.: +31 (0)72 57 27879
 Email: todo@todobv.nl