



NOVAFLEX[®]

PROVIDING HOSE & DUCT SOLUTIONS



ABASION RESISTANT
Dredge Sleeve
Sand Discharge Hose

Novaflex®

Dredge Sleeve Sand Discharge

Novaflex 5331

Dredge Sleeve/Sand Discharge Hose

A specially compounded abrasive resistant and static conductive hose. Hose manufactured to very close O.D. tolerances.

Specifications

Tube: Black abrasion resistant synthetic rubber. Reinforcement: Polyester Tire cord. Cover: Black abrasion and weather resistant synthetic rubber. Length 20 feet. Temperature Range: -40°F (-40°C) to +180°F (+82°C).

Novaflex 5332

Sand Suction Hose

A specially compounded abrasive resistant and static conductive hose. Hose manufactured to very close O.D. tolerances.

Specifications

Tube: Black abrasion resistant synthetic static conductive rubber. Reinforcement: Polyester tire cord with helix wire. Cover: Black abrasion and weather resistant synthetic rubber. Length 20 feet. Temperature Range: -40°F (-40°C) to +180°F (+82°C).

Novaflex 5332YG = Yellow Novaware tube - superior abrasion resistance. Temperature to 160°F (171°C)



| Part No. | I.D. (in) | O.D. (in) | Tube Gauge | Plies | WP psi | WT LBS/FT |
|-----------------|-----------|-----------|------------|-------|--------|-----------|
| 5331BS-04500-00 | 4½ | 5.73 | ¾ | 4 | 150 | 5.45 |
| 5331BS-06000-00 | 6 | 7.25 | ¾ | 4 | 150 | 7.51 |
| 5331BS-06625-00 | 6¾ | 8.07 | ¾ | 6 | 150 | 9.26 |
| 5331BS-08625-00 | 8¾ | 10.19 | ¾ | 8 | 150 | 12.97 |
| 5331BS-10750-00 | 10¾ | 12.50 | ½ | 8 | 150 | 17.83 |
| 5331BS-12775-00 | 12¾ | 14.55 | ½ | 8 | 150 | 22.80 |
| 5331BS-14000-00 | 14 | 16.04 | ½ | 12 | 150 | 27.21 |
| 5331BS-16000-00 | 16 | 18.04 | ½ | 12 | 150 | 30.82 |

| Part No. | I.D. (in) | O.D. (in) | Tube Gauge | Plies | WP psi | WT LBS/FT |
|-----------------|-----------|-----------|------------|-------|--------|-----------|
| 5332BS-04000-00 | 4 | 5.54 | ¾ | 4 | 150 | 6.75 |
| 5332BS-04500-00 | 4½ | 5.95 | ¾ | 4 | 150 | 7.46 |
| 5332BS-06000-00 | 6 | 7.57 | ¾ | 4 | 100 | 11.37 |
| 5332BS-06625-00 | 6¾ | 8.20 | ¾ | 4 | 100 | 12.41 |
| 5332BS-08000-00 | 8 | 9.64 | ¾ | 6 | 100 | 15.86 |
| 5332BS-08625-00 | 8¾ | 10.32 | ¾ | 6 | 100 | 16.87 |
| 5332BS-10000-00 | 10 | 12.06 | ½ | 6 | 100 | 25.42 |
| 5332BS-10750-00 | 10¾ | 12.86 | ½ | 6 | 100 | 22.06 |
| 5332BS-12000-00 | 12 | 14.11 | ½ | 6 | 100 | 30.55 |
| 5332BS-12750-00 | 12¾ | 14.86 | ½ | 6 | 100 | 32.29 |
| 5332BS-14000-00 | 14 | 16.37 | ½ | 8 | 100 | 42.66 |

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

09.2017

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk