

# INSULFLEX®

## Technical Data Sheet

### Thermosleeve™ B

Product Name: Thermosleeve™ B

Technical Description: A flexible, expandable, braided sleeve made from textured E glass yarn.

Temperature Capabilities: Rated for 1000°F (538°C) continuous and intermittent exposure to 1200°F (650°C).

Product Overview: Thermosleeve B is a bulk economy grade fiberglass sleeve that offers maximum thermal efficiency for minimum cost. It is ideal for use as insulation or heat protection of hoses and cables. Thermosleeve B is often used underneath Pyrojacket or Pyreflect sleeve as an effective way of increasing insulation values for minimum cost.

Dimensional Data: Available in .125" (3.2mm) or .0625" (1.58mm) wall thickness. Diameter range is from 1/2" (13mm) to 4" (102mm) diameter.

Installation: Can be installed over almost any hose or cable.

Cautionary Notes: Extended exposure to water or other liquids causes weakening of the fibers. Loose fibers may cause some irritation to skin. Long sleeves, goggles and gloves recommended during installation.



Disclaimer: Due to the range of possible applications, no warranty is expressed or implied. ADL Insulflex, Inc.'s liability is limited solely to the replacement of defective material. ADL Insulflex, Inc. will not be held liable for any consequential damages arising from the use or misuse of the material. While the information given herein is believed to be reliable, ADL Insulflex, Inc. makes no warranties as to the accuracy or completeness. Samples of all Insulflex® products are available at no cost or obligation, and suitable trials should be made prior to installation.

**Telephone**  
North America: 800 461 9323  
International: 905 377 1461

**ADL Insulflex, Inc.**  
8783 Dale Road  
Cobourg, Ontario  
K9A 4J9  
Canada

**Fax**  
North America: 800 461 9328  
International: 905 377 1484