

Novaflex®

Industrial Vacuum Hose

Novaflex 5020

Industrial Vacuum Hose

Designed for light duty commercial vacuum cleaners used in foundries, factories and similar applications where a flexible and lightweight construction is preferred.

Specifications

Tube: 1/16" abrasion resistant Reinforcement: Fabric with helix wire

Cover: Black corrugated

Length 50 ft.

Ends: Plain (Also available with cuffs)

Temperature range: Range: -40°F to +160°F (Depending on

compound)



Specification Chart

Part No.	I.D.	0.D.	Plies	MBR (in)	WT LBS/FT
5020-01000-00	1	1.38	1	3	0.4
5020-01250-00	11/4	1.63	1	4	0.4
5020-01500-00	1½	1.88	1	5	0.5
5020-02000-00	2	2.38	1	8	0.7
5020-02500-00	21/2	2.88	1	8	0.8
5020-03000-00	3	3.38	1	9	0.9
5020-04000-00	4	4.38	1	12	1.9

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

10.2011

IN USA

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

New Jersey

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

Indianapolis

7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

IN CANADA

Whitby, Ontario 119 Consumers Drive Whitby, ON L1N 1C4 tel (905)666-4970 fax (905) 666-9388 800-563-3539

IN U.K.

Bromborough, Wirral

18 Candy Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com