

Novaflex®

Tank Truck Hose

Novaflex 3253

Tank Truck Hose

Nitrile tube designed for use with oil, gasoline and other petroleum products. Ideal for pressure, gravity flow or suction service from tank trucks, tank cars or bulk plants. Steel wire helix is spiraled between multiple plies of tire cord to reinforce hose to resist crushing and kinking. Black neoprene cover is abrasion, oil and weather resistant.

Specifications

Tube: Nitrile

Reinforcement: Multiple plies polyester tire cord and steel wire helix

Cover: Black neoprene

Length: 100 ft.

Temperature Range: -30°F (-35°C) to +180°F (+82°C)



Fuel Compatibility:

Ethanol up to E85

Biodiesel up to B20

Specification Chart

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3253-01250-00	1¼	1.73	2	3	30"	150	0.71
3253-01500-00	1½	1.98	2	3	30"	150	0.80
3253-02000-00	2	2.49	2	4	30"	150	1.08
3253-02500-00	2½	3.01	2	5	30"	150	1.44
3253-03000-00	3	3.57	2	6	30"	150	1.90
3253-04000-00	4	4.57	2	8	30"	150	2.49

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

06.2013

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk