

Novaflex®

Nitrile Suction & Discharge Hose

Novaflex 6309

Nitrile Food 150 Crush Resistant Suction & Discharge Hose

Kink and crush resistant suction and discharge hose. Recommended for the food transfer application that demands both flexibility and ruggedness with a clean white FDA tube. Meets REACH, ADI, FDA, USDA & 3A sanitary standards Authorized #1376. The food grade nitrile tube is odorless and tasteless for those oily transfer applications. Excellent for suction and discharge applications. This ultra smooth microbe resistant tube is built on special stainless steel mandrels for cleanliness.

Construction:

Tube: NBR/White

Reinforcement: 2 ply fabric reinforced, and dual monofilament

helix

Cover: Blue NBR Length: 100ft.

Temperature Range: -40° to +93°C Sizes 1" through 3" are rated full vacuum.

4" is rated to 20 in/hg. Not for continuous steam service.



Specification Chart

Part No.	ID in	ID mm	OD in	OD mm	VAC Bar	PSI	WP Bar	MBR in	MBR mm	Kg/m
6309-01000-00	1	25.4	1.66	42.2	.9	150	10.34	5	127.0	1.16
6309-01500-00	1.5	38.1	2.12	53.8	.9	150	10.34	6	152.4	1.56
6309-02000-00	2	50.8	2.72	69.1	.9	150	10.34	7	177.8	2.31
6309-02500-00	2.5	63.5	3.26	82.8	.9	150	10.34	8	203.2	2.83
6309-03000-00	3	76.2	3.81	96.8	.9	150	10.34	9	228.6	3.42
6309-04000-00	4	101.6	4.81	122.2	.9	150	10.34	14	355.6	4.24

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. For complete guide to proper care, use and maintenance see Care & Maintenance Guide @2003-1 at www.novaflex.com. Please defer to Novaflex terms and conditions of sale located at: www.novaflex.com/TermsConditions/

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk

IN CANADA

Ajax, Ontario

555 Beck Crescent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

IN USA

North Carolina

449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

New Jersey

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

Indianapolis

7812 Moller Road Indianapolis, IN 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288



Email: sales@novaflex.com Website: www.novaflex.com