

Novaflex®

Brewery Discharge Hose

Novaflex 6502

High Pressure, Superior Quality

Brewery Discharge Hose

Novaflex 6502 special construction provides maximum flexibility for ease of handling. The special smooth chlorobutyl bacteria resistant tube designed for non-oily applications will not impart odor or taste. Meets REACH, ADI, FDA, USDA and 3-A (Cert#1803).

Construction:

Tube: White chlorobutyl (non oily applications)

Reinforcement: Multiple plies of polyester synthetic textile

Cover: Red EPDM. Length 100 ft Temperature Range: -40°C to +116°C.

(Cleaning In Place to +120°C). Not for continuous steam

service.



Specification Chart

Part No.	ID in	ID mm	OD in	OD mm	PSI	WP Bar	MBR in	MBR mm	Kg/m
6502WB-00750-00	0.75	19.05	1.34	34.0	350	24.13	n/a	n/a	0.88
6502WB-01000-00	1	25.4	1.68	42.7	350	24.13	n/a	n/a	1.27
6502WB-01500-00	1.5	38.1	2.23	56.6	350	24.13	n/a	n/a	1.86
6502WB-02000-00	2	50.8	2.87	72.9	350	24.13	n/a	n/a	2.81
6502WB-02500-00	2.5	63.5	3.5	88.9	350	24.13	n/a	n/a	4.02
6502WB-03000-00	3	76.2	4.08	103.6	350	24.13	n/a	n/a	5.14
6502WB-04000-00	4	101.6	5.3	134.6	350	24.13	n/a	n/a	8.04

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. For complete guide to proper care, use and maintenance see Care & Maintenance Guide @2003-1 at www.novaflex.com. Please defer to Novaflex terms and conditions of sale located at: www.novaflex.com/TermsConditions/

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk

IN CANADA

Ajax, Ontario

555 Beck Crescent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

IN USA

North Carolina

449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554 800-334-4270

New Jersey

1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385 800-225-0215

Indianapolis

7812 Moller Road Indianapolis, IN 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288



Email: sales@novaflex.com Website: www.novaflex.com