

Novaflex®

Extra Flexible Nitrile Hose

Novaflex 6314WT Extra Flexible Nitrile Food 150 Suction & Discharge Hose

Recommended for the food transfer application (oily and non-oily) that demands both flexibility and ruggedness with a clean white FDA grade tube. Meets FDA, USDA & 3A sanitary standards Authorized #1376. The food grade nitrile tube is odorless and tasteless for those oily transfer applications. This ultra smooth microbe resistant tube is built of special stainless steel mandrels for cleanliness.

Specifications

Tube: FDA white nitrile

Reinforcement: Multiple plies of polyester tire cord with helix wire

Cover: Grey PVC nitrile corrugated

Length: 100 ft.

Temperature Range -40°F (-40°C) to +210°F (+99°C)

Cleaning in Place to 248°F (+120°C) Not for continuous steam service

Corrugated available with UHMWP cover "WTU" for added abrasion resistance. Nova-Glide is an UHMWP cover applied over the rubber cover to provide easy cleaning, low coefficient of friction and added abrasion.



Specification Chart

Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT
6314WT-1500-00	1 1/2	2.05	2	150	2"	1.04
6314WT-1500-00	2	2.55	2	150	3"	1.34
6314WT-1500-00	21/2	3.05	2	150	4"	1.57
6314WT-1500-00	3	3.75	2	150	5"	2.78
6314WT-1500-00	4	4.76	2	150	6.5"	3.82

Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT
6314WTU-1500-00	11/2	2.13	2	150	2.5"	1.05
6314WTU-1500-00	2	2.62	2	150	4"	1.75
6314WTU-1500-00	21/2	3.13	2	150	5"	1.58
6314WTU-1500-00	3	3.85	2	150	6.5"	2.91
6314WTU-1500-00	4	4.86	2	150	8.5"	3.92

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

06.2017

IN USA

North Carolina 449 Trollingwood Road Haw River, NC 27258 tel (336)578-2161 fax (336)578-5554

800-334-4270

New Jersey 1024 Industrial Drive West Berlin, NJ 08091 tel (856)768-2275 fax (856)768-2385

800-225-0215

Indianapolis 7812 Moller Road Indianapolis, IND 46268 tel (317)334-1444 fax (317)334-1535 800-526-6288

IN CANADA

Ajax, Ontario 555 Beck Cresent Ajax, ON L1Z 1C9 tel (905)686-5200 fax (905) 686-8349 800-563-3539

IN U.K.

Bromborough, Wirral 18 Plantation Park 2, Power Road Bromborough, Wirral UK CH62 3QT tel 44(0)151-334-0873 fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk



Email: sales@novaflex.com Website: www.novaflex.com