

Novaflex®

Extra Flexible Hose

Novaflex 6514WB Extra Flexible Connoisseurs Food & Beverage Hose Suction & Discharge

The connoisseur line of food hose is designed to meet the food processing industries demanding applications. Connoisseur is built in a variety of hose constructions utilizing a white chlorobutyl tube for non-oily applications that will not impart taste or odor. Meets FDA, USDA, and 3-A Sanitary Standards Authorized (#1376). Resistant to CIP solutions. This ultra smooth microbe resistant tube is built of special stainless steel mandrels for cleanliness.

Specifications

Tube: White chlorobutyl (full vacuum non oily applications)
Reinforcement: Multiple plies of polyester tire cord with helix wire (microbe resistant)
Cover: Grey EPDM Corrugated
Length: 100 ft.
Temperature Range -40°F (-40°C) to +240°F (+116°C)
Cleaning in Place to 248°F (+120°C) Not for continuous steam service
Corrugated available with UHMWVP cover



Specification Chart

Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT
6514WT-01500-00	1½	2.04	2	150	2"	0.92
6514WT-02000-00	2	2.66	2	150	3"	1.44
6514WT-02500-00	2½	3.231	2	150	4"	1.97
6514WT-03000-00	3	3.82	2	150	5"	2.97
6514WT-04000-00	4	4.82	2	150	7"	3.84

Nova-Glide cover

Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT
6514WEU-01500-00	1½	2.06	2	150	2.5"	.94
6514WEU-02000-00	2	2.57	2	150	3.5"	1.47
6514WEU-02500-00	2½	3.12	2	150	5.5"	2.03
6514WEU-03000-00	3	3.71	2	150	6.5"	3.03
6514WEU-04000-00	4	4.79	2	150	8.5"	3.91

Nova-Glide is an UHMWVP cover applied over the rubber cover to provide easy cleaning, low coefficient of friction and added abrasion.

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

06.2017

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk