



PIG'S TAIL™ PROTECTIVE WRAPPING

FITTING CHART

Part Number	Hose OD Range
R9SSG	.28– .51 in
R12SSG	.39 – .66 in
R16SSG	.47 – .86 in
R20SSG	.62 – 1.06 in
R25SSG	.86 – 1.37 in
R32SSG	1.06 – 1.69 in
R40SSG	1.3 – 2.17 in
R50SSG	1.65 – 2.52 in
R63SSG	2.05 – 2.95 in
R75SSG	2.56 – 3.8 in
R90SSG	3.15 – 4.3 in
R110SSG	3.8 – 4.9 in
R125SSG	4.5 – 5.5in
R140SSG	4.8 – 6.0 in
R160SSG	5.7 – 7.0+ in

Formula for Spiral Length

$$\text{HOSE OD} \div \text{SPIRAL ID} \times \text{HOSE LENGTH} = \text{Spiral Length}$$

Measurement Example:

If you have a 33ft hose with an OD of 1.57 (in), using the recommended R40SSG, which has an ID of 1.26 (in), you would require 41 (ft) of R40SSG.

$$1.57(\text{in}) \text{ Hose} \div 1.26(\text{in}) \text{ ID of R40SSG} \times 33\text{ft} = 41\text{ft of Pig's Tail Wrapping}$$

NOMINAL DIMENSIONS

Part Number	ID (in)		Wall Thickness (in)		Helix – Band Width (in)	
R9SSG	.28	+/- .02	.06	+/- .01	.25	+/- .08
R12SSG	.4	+/- .02	.06	+/- .01	.4	+/- .08
R16SSG	.45	+/- .02	.06	+/- .01	.48	+/- .08
R20SSG	.55	+/- .02	.07	+/- .01	.57	+/- .08
R25SSG	.8	+/- .02	.08	+/- .01	.82	+/- .12
R32SSG	1.0	+/- .02	.09	+/- .01	.94	+/- .12
R40SSG	1.26	+/- .04	.09	+/- .01	1.18	+/- .12
R50SSG	1.5	+/- .04	.12	+/- .01	1.38	+/- .12
R63SSG	2.0	+/- .04	.14	+/- .01	1.57	+/- .16
R75SSG	2.4	+/- .04	.15	+/- .02	1.6	+/- .16
R90SSG	2.83	+/- .04	.18	+/- .02	1.78	+/- .16
R110SSG	3.43	+/- .04	.22	+/- .02	2.17	+/- .16
R125SSG	4.48	+/- .04	.22	+/- .02	2.17	+/- .16
R140SSG	5.07	+/- .04	.22	+/- .02	2.17	+/- .16
R160SSG	5.87	+/- .04	.22	+/- .02	2.36	+/- .16

