

NOVAFLEX[®]

PROVIDING HOSE & DUCT SOLUTIONS



ULTRA ABASION RESISTANT
Mining Slurry Hoses

LARGE DIAMETER CUSTOM
Material Handling Hoses

Novaflex®

Slurry King Material Handling Hose

The solution to your hard piping problems!


Slurry-King is the tough, versatile alternative to inflexible, cumbersome steel tubing. Its easy handling and reusable quick-fastening flange system make installation a snap. So when your hard piping system is down, get up and running in minutes with Slurry-King material handling hose.

- Absorbs system vibration and saves wear on equipment
- Compensates for thermal expansion and contraction
- Reduces noise
- Flexible connection for hard piping misalignment
- Can be cut on site for immediate installation
- No welding necessary!
- Available with many inner tube compounds to meet your specific material handling needs including 'Wear Indicator' style for visual abrasion monitoring
- Available in a variety of tube gauges ranging from: 1/8", 3/16", 1/4", 5/16", 3/8", 1/2"
- Flanges available



Specification Chart

I.D. Inch	O.D. Inch	Lining Thickness Inch	Min Bend Radius	Max Prod Lgth/FT	Working Pressure/PSI	Approx WT/FT
2	3	3/16	12	60	150	2.0
2 1/2	3 1/2	3/8	12	60	150	2.7
3	4 1/2	3/8	14	60	150	4.0
4	5 1/4	3/8	20	60	150	5.4
4 1/2	6 29/64	3/8	26	60	150	9.4
5	6 29/64	3/8	26	60	150	8.0
6	7 1/2	3/8	30	60	150	9.4
8	9 1/2	3/8	69	40	150	12.1
10	11 1/2	3/8	79	40	150	14.8
12	13 3/4	3/8	99	40	150	18.8
14	16	3/8	119	40	150	26.0



'D' I.D. Inches	'A' Inches	'B' Inches	'K' Inches	'P' Inches	'Z' Inches	'H' Inches	Approx/WT/LBS
2	3 11/32	5/8	4 3/4	6	4	3/4	3.3
2 1/2	3 5/16	5/8	5 1/2	7	4	3/4	4.4
3	3 5/16	5/8	6	7 1/2	4	3/4	4.4
4	3 5/16	5/8	7 1/2	9	8	3/4	6.6
4 1/2	4 1/8	5/8	8 1/2	10	8	7/8	7.7
5	4 1/8	5/8	8 1/2	10	8	7/8	7.7
6	4 1/2	1 1/16	9 1/2	11	8	7/8	8.8
8	5 7/8	3/4	11 3/4	13 1/2	8	7/8	13.2
10	6 7/8	1 1/8	14 1/4	16	12	1	25.4
12	7 11/16	1 1/8	17	19	12	1	30.9
14	7 11/16	1 1/8	18 3/4	21	12	1 1/8	35.3

Slurry King Hose Specifications

WEAR-INDICATOR STYLE

Ideal for abrasive applications where preventative maintenance programs are in place. Slurry-King 'wear-indicator' can be disconnected on site for routine visual wear monitoring: When the alternating black and red tube compounds have worn down to the next layer the hose is simply rotated for extended life. **Disclaimer:** It is impossible to test Novaflex hose and ducting under all conditions to which it might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and ducting under conditions that duplicate the service condition prior to installation.

Split Flange Coupling Specifications

09.2016

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indiana

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Candy Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145

www.novaflex.co.uk Email: sales@novaflex.co.uk