

PVC GREEN STANDARD SUCTION HOSE

SPIRALITE® 110-00



(<http://d9076884.u118.c14.ixinstant.com/wp-content/uploads/110-00.gif>)

DESCRIPTION

PVC Green Standard Suction Hose

APPEARANCE / CONSTRUCTION:

Green PVC with white helix. Smooth wall and interior.

BENEFITS:

- Highly versatile and durable
- Smooth interior prevents material blockage

GENERAL APPLICATIONS:

-General suction for water and light chemical solutions

TEMPERATURE RANGE:

-10F TO +130F

STANDARD LENGTHS:

3/4" through 6" 100 feet
8" and above 20', 25', 30'

NOMINAL SIZE (inch)	Approx OD (inch)	Rec WP @ 72° F (psi)	Approx WP @ 140° F (psi)	Vacuum Rating (in/Hg)	Rec Min Bend Radius @ 72° F (inch)	Approx Burst Pressure @ 72° F (psi)	Approx Weight (lbs/ft)
3/4	1.01	100	42	28	2	300	.20
1	1.27	90	42	28	3	300	.27
1-1/4	1.53	90	42	28	4	270	.36
1-1/2	1.82	90	42	28	5	270	.47
2	2.36	70	37	28	6	210	.636
2-1/2	2.98	65	32	28	8	195	.92
3	3.44	55	28	28	9	165	1.20
4	4.52	50	28	28	13	150	1.87
5	5.65	45	-	28	21	135	3.00
6	6.80	45	-	28	24	135	4.56
8	8.95	40	-	28	35	120	7.05
10	11.34	40	-	28	41	120	12.37
12	13.39	35	-	26	53	105	15.66

HEADQUARTERS

23540 Telo Avenue
Torrance, CA 90505

(310) 539-1822

sales@pacificecho.com

WAREHOUSE LOCATIONS

Elk Grove Village, IL
Houston, TX
Atlanta, GA

SEARCH

PRODUCTS

- > SPIRALITE Hoses
 - > Industrial Hoses
 - > Spa-Flex Hoses
 - > Pond-Flex Hoses
- > Clamps

GET IN TOUCH

Name:

Email:

Phone:

Comment: