



Products Manufacturer of industrial, pool and landscaping hoses

PVC CLEAR STANDARD SUCTION HOSE

SPIRALITE® 115-00

NOMINAL SIZE (inch)	Approx OD (inch)	Rec WP @ 72° F (psi)	WP @ 149	Vacuum Rating (in/Hg)	Rec Min Bend Radius @ 72° F (inch)	Approx Burst Pressure @ 72° F (psi)	Approx Weight (lbs/ft)
3/4	1.02	100	42	28	2	300	.21
1	1.29	90	42	28	3	300	.29
1-1/4	1.53	90	42	28	4	270	.38
1-1/2	1.84	90	42	28	4	270	.49
2	2.39	70	37	28	5	210	.71
2-1/2	2.92	65	32	28	7	195	.98
3	3.46	55	28	28	8	165	1.28
4	4.56	50	28	28	12	150	2.02
5	5.65	45	-	28	20	135	2.97
6	6.80	45	-	28	23	135	4.39
8	8.95	40	-	28	34	120	6.79
10	11.34	40	-	28	40	120	11.88
12	13.19	35	-	28	50	105	15.07

DESCRIPTION

PVC Clear Standard Suction Hose

APPEARANCE / CONSTRUCTION:

Clear PVC with white helix. Smooth wall and interior.

BENEFITS:

- Highly versatile and durable
- Smooth interior prevents material blockage
- Clear wall allows easy inspection

GENERAL APPLICATIONS:

-General suction for water and light chemical solutions

TEMPERATURE RANGE:

-10F TO +130F

STANDARD LENGTHS:

3/4" through 6" 100 feet
8" and above 20', 25', 30'

HEADQUARTERS

23540 Telo Avenue
Torrance, CA 90505

(310) 539-1822

sales@pacificecho.com

WAREHOUSE LOCATIONS

Elk Grove Village, IL
Houston, TX
Atlanta, GA

SEARCH

PRODUCTS

GET IN TOUCH

Name:

Email:

Phone:

- > SPIRALITE Hoses
- > Industrial Hoses
- > Spa-Flex Hoses
- > Pond-Flex Hoses
- > Clamps

Comment:

submit