



PVC OIL RESISTANT CORRUGATED SUCTION HOSE

SPIRALITE® 160-00

NOMINAL SIZE (inch)	Approx OD (inch)	Approx WP @ 140° F (psi)	Vacuum Rating (in/Hg)	Rec Min Bend Radius @ 72° F (inch)	Approx Weight (lbs/ft)
1-1/2	1.86	50	28	3	.39
2	2.44	40	28	4	.60
2-1/2	2.98	35	28	5	.81
3	3.54	35	28	6	1.10
4	4.65	35	28	8	1.73

DESCRIPTION

PVC Oil Resistant Corrugated Suction Hose

APPEARANCE / CONSTRUCTION:

Orange PVC with white helix. Corrugated wall, smooth interior

BENEFITS:

-Specially compounded from oil-resistant PVC

-Excellent alternative to more expensive rubber hose in certain applications

GENERAL APPLICATIONS:

-General suction of light oils and animal fats

-Good for use in environments where hose may be exposed to oils

-Vapor recovery

TEMPERATURE RANGE:

-10F TO +130F

STANDARD LENGTHS:

1-1/2" through 4" 100 feet

HEADQUARTERS

23540 Telo Avenue
Torrance, CA 90505

WAREHOUSE LOCATIONS

Elk Grove Village, IL
Houston, TX
Atlanta, GA

SEARCH

GET IN TOUCH

Name:

(310) 539-1822

sales@pacificecho.com

PRODUCTS

- > SPIRALITE Hoses
 - > Industrial Hoses
 - > Spa-Flex Hoses
 - > Pond-Flex Hoses
- > Clamps

Email:

Phone:

Comment: