



Products Manufacturer of industrial, pool and landscaping hoses

BRAIDED CLEAR PVC CORRUGATED HOSE

SPIRALITE® 6200-00

NOMINAL SIZE (inch)	Approx OD (inch)	Recom. Rec WP @ 72° F (psi)	Approx Burst Pressure @ 72° F (psi)	Vacuum Rating @ 72° F (in/Hg)	Rec Min Bend Radius @ 72° F (inch)	Approx Weight (lbs/ft)
1	1.38	100	400	28	3	.27
1-1/4	1.66	100	400	28	3	.33
1-1/2	1.89	100	280	28	4	.36
2	2.45	100	280	28	5	.54
3	3.61	100	280	28	7	1.07
4	4.73	75	200	28	8	1.74
6	7.13	70	180	28	12	3.81
8	9.30	50	150	28	30	5.00
10	11.50	35	105	28	44	7.48
12*	13.77	30	100	25	80	11.25

*12" size available in ORANGE helix only.

DESCRIPTION

Braided Clear PVC Corrugated Hose

APPEARANCE / CONSTRUCTION:

- Clear, braid-reinforced PVC tube with white rigid PVC helix
- Also available with **ORANGE** helix (6200-90)
- Available in FOOD-GRADE version (6250). WHITE helix only

BENEFITS:

- Clear wall allows easy inspection of material flow
- Smooth interior prevents material blockage
- Exterior helix reduces resistance when dragging
- Braided construction increases working pressure and tensile strength

GENERAL APPLICATIONS:

- Suction and discharge for water and light chemical solutions
- Winery, Dairy and other food applications (6250 Only!)

TEMPERATURE RANGE:

-10F TO +130F

STANDARD LENGTHS:

- 1" through 6" 100 feet
- 8" and above 20', 25', 30', 40'

HEADQUARTERS

23540 Telo Avenue
Torrance, CA 90505

(310) 539-1822

sales@pacificecho.com

WAREHOUSE LOCATIONS

Elk Grove Village, IL
Houston, TX
Atlanta, GA

SEARCH

PRODUCTS

- > SPIRALITE Hoses
 - > Industrial Hoses
 - > Spa-Flex Hoses
 - > Pond-Flex Hoses
- > Clamps

GET IN TOUCH

Name:

Email:

Phone:

Comment: