



POLYURETHANE LINED PVC SUCTION HOSE

SPIRALITE® U125-05

| NOMINAL SIZE (inch) | Approx OD (inch) | Rec WP @ 72° F | Vacuum Rating @ 72° (in/Hg) | Rec Min Bend Radius @ 72° F (inch) | Approx Burst Pressure @ 72° F (psi) | Approx Weight (lbs/ft) |
|---------------------|------------------|----------------|-----------------------------|------------------------------------|-------------------------------------|------------------------|
| 1-1/2 | 2.07 | 100 | 28 | 4 | 300 | .55 |
| 2 | 2.66 | 100 | 28 | 4 | 310 | .88 |
| 3 | 3.86 | 85 | 28 | 6 | 260 | 1.48 |
| 4 | 4.87 | 70 | 28 | 8 | 210 | 2.30 |

DESCRIPTION

Polyurethane Lined PVC Suction Hose

APPEARANCE / CONSTRUCTION:

-Black PVC wall with white rigid PVC helix. Smooth interior tube with polyurethane lining

-Also available in CLEAR version (U125-00)

BENEFITS:

-Excellent abrasion resistance and flexibility

GENERAL APPLICATIONS:

-Abrasive material handling

-Short blast recovery

-Industrial vacuums

-Pellet & grain transfer

TEMPERATURE RANGE:

-30F TO +130F

STANDARD LENGTHS:

2" through 4" 100 feet

HEADQUARTERS

23540 Telo Avenue
Torrance, CA 90505

(310) 539-1822

WAREHOUSE LOCATIONS

Elk Grove Village, IL
Houston, TX
Atlanta, GA

SEARCH

PRODUCTS

GET IN TOUCH

Name:

Email:

- > SPIRALITE Hoses
- > Industrial Hoses
- > Spa-Flex Hoses
- > Pond-Flex Hoses
- > Clamps

Phone:

Comment: